



NASIOL NL272, ZR53, XR03, Metalcoat F2, GLASSHIELD WIPE ON - LIMITED WARRANTY

(Nasiol is a Registered Trademark of Artekya Teknoloji Ltd.)

Congratulations on coating your vehicle with **Nasiol's** world leading nano ceramic paint protection system/s.

The nano protective layer provided by **Nasiol** is certified to last and be effective for a period of:

- 5 (five) years in respect of **Nasiol NL272**
- 3 (three) years in respect of **Nasiol ZR53**
- 18 (eighteen) months in respect of **Nasiol XR03**
- 12 (twelve) months in respect of **Nasiol Metalcoat F2**
- 12 (twelve) months in respect of **Nasiol Glassshield Wipe On**

The projected durability of the **Nasiol** product is calculated from the date of initial application and is warranted as such subject to the following terms and conditions:

- The product must be applied by an accredited **Nasiol Fitment Centre** or certified **Nasiol Applicator** in accordance with the manufacturer's application guidelines.
- The vehicle must be operated under normal operating conditions. Whilst the product provides paint scratch protection to a hardness factor of 10H (**Nasiol NL272 / Nasiol ZR53**) and 7H (**Nasiol XR03, Nasiol Metalcoat F2 / Nasiol Glassshield Wipe On**) as certified by **TUV Rheinland**, it cannot protect the paintwork against more robust abrasion and larger stone chips.
- The vehicle must be washed and cared for in accordance with the **Nasiol After Care Guidelines** provided.
- The vehicle should only be washed using **Nasiol Cleanion Pro** or similar pH neutral vehicle shampoo. The vehicle must also not be waxed or polished once nano coated.
- Vehicle paint resprays will invalidate this warranty unless the vehicle is recoated with the same **Nasiol** product that was originally applied in respect of which this warranty has been given which should be applied no sooner than 30 (thirty) days following such respray to allow the respray to properly cure.
- This warranty will be invalidated if the vehicle has been washed using borehole water or has been exposed to damaging or corrosive chemicals.
- This warranty is subject to the vehicle being nano coated using only original **Nasiol** products, packaged in an original **Nasiol** sealed and packed box set which must be used within one week of opening the seal on the box set. Under no circumstances should these products be decanted or repackaged. In such instances, the warranty will be invalidated. The warranty will also be invalidated should such **Nasiol** products be used more than one week after opening the product. (Nasiol's Bulk packaged products which are intended for industrial applications only are not suitable for automotive use and, accordingly, are not warranted for use on motor vehicles).
- This warranty is subject to the vehicle undergoing an annual maintenance check with an accredited **Nasiol Fitment Centre** or certified **Nasiol Applicator**.

- **IMPORTANT** - Customers are required to report any concerns, defects or imperfections related to the application of the **Nasiol** product to their **Nasiol** accredited applicator within 7 (seven) days from the date of application of the **Nasiol** product. Due to the difficulty in assessing the underlying cause and responsibility for any damage that may be caused to the **Nasiol** coating beyond this period, the **Nasiol** accredited applicator cannot be held responsible for any such application concerns, imperfections or defects beyond this initial 7 (seven) day period.
- **IMPORTANT** – Regarding motorcars, the original **Nasiol** box set applied by the accredited **Nasiol Applicator** to the motorcar and its entire left-over contents must be provided to the motorcar's owner following the product's application. Each box set must only be applied to **ONE** motorcar and the applicator must ensure that sufficient **Nasiol** product is applied to the motorcar in line with the product's application instructions and guidelines per the product's **Technical Data Sheet**.
- Regarding motorcars, this warranty is subject to the return to **Epik Trading (Pty) Ltd.** (the appointed, exclusive Southern African distributors of the **Nasiol** product range) of the original product box set used for the **Nasiol** product application as well as its entire left-over contents for which the warranty is being claimed. Each box set displays a unique serial number.
- Regarding vehicles other than motorcars such as motorcycles, watercraft, and aircraft, the **Nasiol applicator** must adhere to the product's "**Consumption per Unit Area**" guideline as detailed in the **Technical Data Sheet** for that product.

Should this product's performance be defective in any way or should the product's durability fall short of the certified, effective performance, a new, replacement box set of the **Nasiol** product will be provided subject to the condition that it is used only as a recoating on the same vehicle whereby the defect or fall-off in durability has been experienced. Accordingly, the replacement product may not be used on a different vehicle from the one for which this warranty was extended.

Contact your accredited **Nasiol Fitment Centre** or certified **Nasiol Applicator** for annual maintenance and repairs.



NASIOL'S AFTER CARE GUIDELINES

(Nasiol is a Registered Trademark of Artekya Teknoloji Ltd.)

CONGRATULATIONS ON CHOOSING **NASIOL'S** WORLD LEADING NANOTECH CERAMIC PAINT PROTECTION SYSTEM FOR YOUR VEHICLE

We trust that you will enjoy many successful years of safe and enjoyable motoring which we are confident will be greatly enhanced by your choice of **Nasiol's** nanotech ceramic paint protection system.

To ensure the best performance from your **Nasiol** product, the following basic care and maintenance procedures are advised.

- When washing your vehicle, we recommend that you only use **Nasiol Cleanion Pro** car shampoo or similar pH neutral car shampoo. Avoid chemical cleaning products with a high (alkaline) pH. The vehicle must also not be waxed or polished once nano coated.
- Use a quality soft microfibre cloth to apply the car shampoo, to remove dirt and to dry off excess water. Avoid all abrasive washing methods, especially mechanical car washes.
- Washing your vehicle with borehole water having a high alkaline content can cause damaging water spotting to vehicle paintwork and coatings. Where a vehicle has been in contact with borehole water, dry the water off the surface with a soft, dry microfibre cloth as soon as possible.
- The "two bucket" washing method is recommended. One bucket contains soapy water whilst the other bucket contains clean water. After applying the soapy water with a microfibre cloth to an area of the car, rinse the microfibre cloth in the bucket with the clean water to remove any lingering dirt and grit on the microfibre cloth before re-plunging it into the soapy bucket in order to wash the next section of the vehicle.
- Your **Nasiol** product will impart a beautiful glossy finish to your vehicle's bodywork, protecting and bringing out the best in the upper clear coat paint layer of your vehicle for years to come. There is no need and it is strongly recommended that no wax products be applied to your **Nasiol** coated vehicle. It is likely that a wax layer will dull the vehicle's unrivalled **Nasiol** nano ceramic gloss finish. The vehicle must also not be polished once nano coated with any **Nasiol** product as the polishing process can potentially remove layers of the nano coating.
- Contact your **Nasiol** accredited applicator for annual maintenance checks and repairs.

By following these easy steps, you will enjoy many years of exceptional performance from your **Nasiol** nanotech ceramic paint protection system.